

HYDRAULIC PRESSHEAD RHU450

crimping force 50.5 sh ton

Hydraulic presshead complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max.

Adaptor type AU 450-130D is available as an optional extra enabling the head to utilise the semi-circular slotted dies which are common to most 12 tons tools (U dies).



HYDRAULIC PRESSHEAD RHU450

Technical characteristics

PROPERTIES

Width	4.72 in.
Length	10.24 in.
Weight	22.66 lbs.
Nominal pressure	10150 psi
Force developed	450 kN
Type of action	Crimp



HYDRAULIC PRESSHEAD RHU450

Products used together

Connectors

COPPER TUBE CRIMPING LUGS ACCORDING TO DIN 46235 DR

DR10-10	DR10-5	DR10-6
DR10-8	DR120-10	DR120-12
DR120-16	DR120-20	DR120-8
DR150-10	DR150-12	DR150-16
DR150-20	DR16-10	DR16-12
DR16-5	DR16-6	DR16-8
DR185-10	DR185-12	DR185-16
DR185-20	DR240-10	DR240-12
DR240-16	DR240-20	DR25-10
DR25-12	DR25-6	DR25-8
DR300-12	DR300-16	DR300-20
DR35-10	DR35-12	DR35-16
DR35-6	DR35-8	DR400-12
DR400-16	DR400-20	DR500-12
DR500-16	DR500-20	DR50-10
DR50-12	DR50-16	DR50-6
DR50-8	DR625-20	DR70-10
DR70-12	DR70-16	DR70-20
DR70-8	DR95-10	DR95-12
DR95-16	DR95-20	DR95-8

Through connectors

CRIMPING THROUGH CONNECTORS ACCORDING TO DIN 46267 T.1 DSV

DSV10	DSV120	DSV150
DSV16	DSV185	DSV240
DSV25	DSV300	DSV35
DSV400	DSV50	DSV500
DSV6	DSV625	DSV70
DSV95		

In the same kit

Storage

CASE VAL - Metallic case storage VAL 450